

17. Mechanical vibrations, part 1: free undamped motion (Notes on Diffy Qs, 2.4)

Jiří Lebl

Oklahoma State University

The textbook: <https://www.jirka.org/diffyqs/>

Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Mass on a spring:

t = time in seconds.

$x(t)$ = displacement from rest, in meters.


m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.

Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.



Mass on a spring:

t = time in seconds.

$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.


k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.

Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.



Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.

Newton's second law: Force equals mass times acceleration:

$$mx'' = F(t) - cx' - kx$$

Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.

Newton's second law: Force equals mass times acceleration:

$$mx'' = F(t) - cx' - kx \quad \text{or} \quad mx'' + cx' + kx = F(t).$$

Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.

Newton's second law: Force equals mass times acceleration:

$$mx'' = F(t) - cx' - kx \quad \text{or} \quad mx'' + cx' + kx = F(t).$$

Second order, linear, constant coefficient ODE.

Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.

Newton's second law: Force equals mass times acceleration:

$$mx'' = F(t) - cx' - kx \quad \text{or} \quad mx'' + cx' + kx = F(t).$$

Second order, linear, constant coefficient ODE.

Motion is: *forced* if $F \not\equiv 0$, and *unforced* or *free* if $F \equiv 0$

Mass on a spring:

t = time in seconds.


$x(t)$ = displacement from rest, in meters.

m = mass in kilograms.

k = spring constant in newtons per meter.

c = damping (friction) in newton-seconds per meter.

$F(t)$ = external force on the mass in newtons.



Hooke's law: Force exerted by the spring is proportional to compression spring: $-kx$.

Force exerted by damping is proportional to the velocity of mass: $-cx'$.

Newton's second law: Force equals mass times acceleration:

$$mx'' = F(t) - cx' - kx \quad \text{or} \quad mx'' + cx' + kx = F(t).$$

Second order, linear, constant coefficient ODE.

Motion is: *forced* if $F \not\equiv 0$, and *unforced* or *free* if $F \equiv 0$

damped if $c > 0$, and *undamped* if $c = 0$.

RLC circuit:

Resistor: R ohms.


Inductor: L henries.

Capacitor: C farads.

Electrical source: $E(t)$ volts.

$Q(t)$ = charge on the capacitor in coulombs.

$I(t)$ = current in the circuit in amperes.



RLC circuit:

Resistor: R ohms.

Inductor: L henries.


Capacitor: C farads.

Electrical source: $E(t)$ volts.

$Q(t)$ = charge on the capacitor in coulombs.

$I(t)$ = current in the circuit in amperes.

The basic relationships: $Q' = I$ and $LI' + RI + Q/c = E$.



RLC circuit:

Resistor: R ohms.

Inductor: L henries.

Capacitor: C farads.

Electrical source: $E(t)$ volts.


$Q(t)$ = charge on the capacitor in coulombs.

$I(t)$ = current in the circuit in amperes.

The basic relationships: $Q' = I$ and $LI' + RI + Q/C = E$.

Differentiate to get

$$LI''(t) + RI'(t) + \frac{1}{C}I(t) = E'(t).$$




Linearized pendulum:

m = mass.

$\theta(t)$ = angle the pendulum makes with vertical.

L = length of the pendulum (meters).

g = force of gravity.



Linearized pendulum:

m = mass.


$\theta(t)$ = angle the pendulum makes with vertical.

L = length of the pendulum (meters).

g = force of gravity.

Via Newton's second: force $-mg \sin \theta$ equals mass m times acceleration $L\theta''$:

$$mL\theta'' = -mg \sin \theta$$



Linearized pendulum:

m = mass.


$\theta(t)$ = angle the pendulum makes with vertical.

L = length of the pendulum (meters).

g = force of gravity.

Via Newton's second: force $-mg \sin \theta$ equals mass m times acceleration $L\theta''$:

$$mL\theta'' = -mg \sin \theta \quad \text{or} \quad \theta'' + \frac{g}{L} \sin \theta = 0.$$



Linearized pendulum:

m = mass.

$\theta(t)$ = angle the pendulum makes with vertical.


L = length of the pendulum (meters).

g = force of gravity.

Via Newton's second: force $-mg \sin \theta$ equals mass m times acceleration $L\theta''$:

$$mL\theta'' = -mg \sin \theta \quad \text{or} \quad \theta'' + \frac{g}{L} \sin \theta = 0.$$

Nonlinear!



Linearized pendulum:

m = mass.

$\theta(t)$ = angle the pendulum makes with vertical.

L = length of the pendulum (meters).



g = force of gravity.

Via Newton's second: force $-mg \sin \theta$ equals mass m times acceleration $L\theta''$:

$$mL\theta'' = -mg \sin \theta \quad \text{or} \quad \theta'' + \frac{g}{L} \sin \theta = 0.$$

Nonlinear!

But! For θ small, $\theta \approx \sin \theta$



Linearized pendulum:

m = mass.

$\theta(t)$ = angle the pendulum makes with vertical.

L = length of the pendulum (meters).

g = force of gravity.

Via Newton's second: force $-mg \sin \theta$ equals mass m times acceleration $L\theta''$:



$$mL\theta'' = -mg \sin \theta \quad \text{or} \quad \theta'' + \frac{g}{L} \sin \theta = 0.$$

Nonlinear!

But! For θ small, $\theta \approx \sin \theta$

So as long as θ is small we have roughly:

$$\theta'' + \frac{g}{L} \theta = 0.$$



We consider free motion, $F \equiv 0$.

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t)$$

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

ω_0 is the (natural) *angular frequency* (radians per time).

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

ω_0 is the (natural) *angular frequency* (radians per time).

$C = \sqrt{A^2 + B^2}$ is the *amplitude*.

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

ω_0 is the (natural) *angular frequency* (radians per time).

$C = \sqrt{A^2 + B^2}$ is the *amplitude*.

γ is the *phase shift*.

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

ω_0 is the (natural) *angular frequency* (radians per time).

$C = \sqrt{A^2 + B^2}$ is the *amplitude*.

γ is the *phase shift*.

Note: *frequency* (cycles per unit time) is angular frequency over 2π (radians per cycle): $\frac{\omega_0}{2\pi}$.

We consider free motion, $F \equiv 0$. We start with free undamped motion, $c = 0$:

$$mx'' + kx = 0.$$

Let $\omega_0 = \sqrt{k/m}$ and write

$$x'' + \omega_0^2 x = 0.$$

The general solution is the *simple harmonic motion*:

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t) \quad \text{or} \quad x(t) = C \cos(\omega_0 t - \gamma)$$

First form easier to solve for initial conditions, second form natural.

ω_0 is the (natural) *angular frequency* (radians per time).

$C = \sqrt{A^2 + B^2}$ is the *amplitude*.

γ is the *phase shift*.

Note: *frequency* (cycles per unit time) is angular frequency over 2π (radians per cycle): $\frac{\omega_0}{2\pi}$.

Note: *period* is the reciprocal of *frequency* (time of one cycle): $\frac{2\pi}{\omega_0}$.

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.
The setup sits on a truck travelling at 1 m/s .

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.
The setup sits on a truck travelling at 1 m/s .
The truck crashes and suddenly stops.

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

$$\text{Frequency in Hertz: } 2/2\pi = 1/\pi \approx 0.318.$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

$$\text{Frequency in Hertz: } 2/2\pi = 1/\pi \approx 0.318.$$

$$\text{The general solution is: } x(t) = A \cos(2t) + B \sin(2t).$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

$$\text{Frequency in Hertz: } 2/2\pi = 1/\pi \approx 0.318.$$

The general solution is: $x(t) = A \cos(2t) + B \sin(2t)$.

$$x(0) = 0.5 \quad \Rightarrow \quad A = 0.5.$$

$$x'(t) = -2(0.5) \sin(2t) + 2B \cos(2t). \quad x'(0) = 1 \quad \Rightarrow \quad B = 0.5.$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

$$\text{Frequency in Hertz: } 2/2\pi = 1/\pi \approx 0.318.$$

The general solution is: $x(t) = A \cos(2t) + B \sin(2t)$.

$$x(0) = 0.5 \quad \Rightarrow \quad A = 0.5.$$

$$x'(t) = -2(0.5) \sin(2t) + 2B \cos(2t). \quad x'(0) = 1 \quad \Rightarrow \quad B = 0.5.$$

$$\text{The amplitude is } C = \sqrt{A^2 + B^2} = \sqrt{0.25 + 0.25} = \sqrt{0.5} \approx 0.707 \text{ meters.}$$

Example: Suppose $m = 2 \text{ kg}$ and $k = 8 \text{ N/m}$.

The setup sits on a truck travelling at 1 m/s .

The truck crashes and suddenly stops.

The mass was 0.5 meters forward from the rest position and got loose during the crash and is now moving forward at 1 m/s .

What is the frequency of the oscillation?

What is the amplitude?

The problem is

$$2x'' + 8x = 0, \quad x(0) = 0.5, \quad x'(0) = 1.$$

$$\text{Angular frequency } \omega_0 = \sqrt{k/m} = \sqrt{4} = 2.$$

$$\text{Frequency in Hertz: } 2/2\pi = 1/\pi \approx 0.318.$$


The general solution is: $x(t) = A \cos(2t) + B \sin(2t)$.

$$x(0) = 0.5 \Rightarrow A = 0.5.$$

$$x'(t) = -2(0.5) \sin(2t) + 2B \cos(2t). \quad x'(0) = 1 \Rightarrow B = 0.5.$$

The amplitude is $C = \sqrt{A^2 + B^2} = \sqrt{0.25 + 0.25} = \sqrt{0.5} \approx 0.707$ meters.

Solution is: $x(t) = 0.5 \cos(2t) + 0.5 \sin(2t)$



For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$?

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$? Check signs: Both A and B were positive so, (A, B) is in the first quadrant, no need to add π .

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$? Check signs: Both A and B were positive so, (A, B) is in the first quadrant, no need to add π . $\gamma = \pi/4$.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$? Check signs: Both A and B were positive so, (A, B) is in the first quadrant, no need to add π . $\gamma = \pi/4$.

Basically, if $A > 0$, don't add π , if $A < 0$, then add or subtract π .

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$? Check signs: Both A and B were positive so, (A, B) is in the first quadrant, no need to add π . $\gamma = \pi/4$.

Basically, if $A > 0$, don't add π , if $A < 0$, then add or subtract π . If $A = 0$, then if $B > 0$, $\gamma = \pi/2$, if $B < 0$, then $\gamma = -\pi/2$.

For free undamped motion, solution is

$$x(t) = A \cos(\omega_0 t) + B \sin(\omega_0 t),$$

where $x(0) = A$ and $x'(0) = \omega_0 B$.

Amplitude $C = \sqrt{A^2 + B^2}$.

γ is a bit harder: $\tan \gamma = B/A$,

One takes the arctangent but that could be π off.

In the example $\tan \gamma = 1$. $\arctan 1 = \pi/4$.

Is $\gamma = \pi/4$? Check signs: Both A and B were positive so, (A, B) is in the first quadrant, no need to add π . $\gamma = \pi/4$.

Basically, if $A > 0$, don't add π , if $A < 0$, then add or subtract π . If $A = 0$, then if $B > 0$, $\gamma = \pi/2$, if $B < 0$, then $\gamma = -\pi/2$.

Calculators and computer software often have a function like $\text{atan2}(A, B)$ that computes γ .